

DFC 24

Schalterfunktion des 8 - poligen DIL - Schalters

1.) Schalttemperaturdifferenz

S1	S2	S3	Temperaturdifferenz
OFF	OFF	OFF	2 Grad
ON	OFF	OFF	4
OFF	ON	OFF	6
ON	ON	OFF	8
OFF	OFF	ON	10
ON	OFF	ON	12
OFF	ON	ON	14
ON	ON	ON	16

2.) Aktivtemperatur

S4	Aktivtemperatur
OFF	80 (70 BEI DFC24S)
ON	100

3.) Wartezeit

S5	S6	S7	Minuten
OFF	OFF	OFF	2.5
ON	OFF	OFF	5.0
OFF	ON	OFF	7.5
ON	ON	OFF	10.0
OFF	OFF	ON	12.5
ON	OFF	ON	15.0
OFF	ON	ON	17.5
ON	ON	ON	20.0

4.) Ablaufgeschwindigkeit

S8	Geschwindigkeit
OFF	Normale Geschwindigkeit
ON	10 - fache Geschwindigkeit

Schalterstellung bei Auslieferung:

1	2	3	4	5	6	7	8	6 Grad Differenz
OFF	ON	OFF	OFF	ON	ON	OFF	OFF	80 Grad Aktivtemp.
								10 Minuten Wartezeit.